

COMPACT LOADER

EDGE® SILAGE DEFACER

The EDGE silage defacer is perfect for farmers with open-pit silage bunkers. It reduces spoilage by exposing less surface area to air and moisture. The open design allows operators to see the bunker face when working.

OPERATIONAL BASICS

The EDGE silage defacer is easy to maintain with a rachet cam chain tension adjustment. The extended frame allows for reach 10 feet (3048 mm) beyond the compact loader lift height. Adjustable guides allow for a cutting depth of 3 inches (76.2 mm). The silage defacer comes complete with hoses and flat face couplers.



SPECIFICATION

Model	Weight (Ibs/kg)	Hyd. Req. (gpm/lpm)	Overall Width (in/mm)	Reach (in/mm)	Digging Depth (in/mm)		
SF96	1100/499	18-22/68-83	96/2438	120/3048	3/76		

FEATURES

- Extended frame for reach 10' (3048 mm) beyond compact loader lift height
- Full 96" (2438 mm) width cut for ease of cutting close to stall walls
- Adjustable guides for a cutting depth of 3" (76.2 mm)
- Abrasion-resistant, high-strength cutter

	Radial Skid Loaders						Vertical Skid Loaders		Track Loaders			Articulated Loaders					
Machine Compatibility Gehl / Mustang	3640E/ 2026						R260/ 2600R	V270/ 2700V	V330 3300V		RT175/ 1750RT			-3/1()	540	650/ 608	
*Silage Defacer					+	+	+	•	•	*	*	*	•			•	•

^{*}Note: Machine compatibility is based on operating capacity of the machine and the weight of the attachment

